

RELIABLE AND QUICK, INSTALLATION ON PITCHED ROOFS



SLATE ROOF

www.esdec.com

THE 4 COMPONENTS OF **CLICKFIT EVO SLATE ROOF**



1. SLATE HOOK

- Fully pre-assembled slate hook
 Extra thin slate hook (4mm) for mounting under the slate.
 Mounting by tightening two flat-head screws, with a slotted hole to make it easier to find the right place for the screw on the
- substructure. Rotatable click connection; self-aligning with integrated cable management
- For both landscape and portrait orientation
 Stepless adjustment of height.




2. MOUNTING RAIL

- Quick and easy to click into the ClickFit EVO click connection on the hook
- Available in different lengths
- Rails can be coupled with a coupler



3. UNIVERSAL MODULE CLAMP

- Universal module clamp: suitable for solar panels with a frame . thickness between 30 and 50 mm
- Can be used as centre clamp or as end clamp in combination with end cap
- Standard assembly
- Including bonding for the solar panels
 Available in grey and black



4. END CAP

- End cap holds the module clamp in its position
- Elongated end cap to allow for aesthetically pleasing finish .
- Available in grey and black





EASY INSTALLATION ON THE ROOF

ClickFit EVO Slate Roof: quick & easy

ClickFit EVO Slate Roof has been specially developed for mounting the popular ClickFit EVO system on slate roofs. Since the mounting system consists of only 4 components and standard solar panels can be mounted on slate roofs with only 1 tool, with ClickFit EVO you can mount the solar panels on the roof in next to no time! The hooks are preassembled and already fitted with the familiar ClickFit EVO click connection to fix the rails to the slate roof hook. This saves you a lot of installation time.

Slate roofs: a specialist job

The ClickFit EVO system is suitable for many types of slate roof. Our flat hook, which is only 4mm thick, makes it easy to install on slate roofs with a substructure of trusses, battens, solid wood or concrete. Our slate hook is unfortunately not suitable for slate roofs with thicker slates, such as Rosemary or Beavertail slates.

Our tip: to make slate roofs watertight again after installing the mounting system, specialist knowledge of slate roofs is required. Before you start, contact a slate roofing specialist to discuss the project!

Description Both horizontal and vertical rails possible

Thanks to the rotatable ClickFit EVO click connection on the slate hook, the mounting system can be installed in both landscape and portrait orientation with both a horizontal and vertical rail. This offers all the flexibility to optimally mount the panels on the roof whatever the conditions.

ADVANTAGES FOR THE INSTALLER

- ✓ Pre-assembled roof hook with rail clicker
- ✓ Only 4 components on the roof
- ✓ Only one tool needed for the mounting system
- 🤣 Quick and easy installation
- 🤣 20-year product warranty

ADVANTAGES FOR YOUR CUSTOMER

- ✓ Quick mounting
- Soth landscape and portrait orientation possible
- Aesthetic design, also available in black
- Extensively tested product
- 🤣 20-year product warranty



1 Assembled hook with height adjustment

Quick and easy mounting with the assembled hook that already has the EVO click connection on it. When mounting on a solid substructure or rafters, with the slotted hole you can offset the second screw, reducing the risk of splitting the underlying batten Additionally, the hook has a stepless height adjustment to correct a certain degree of roof sagging.

2 Unique click connection

The hook is equipped with a self-aligning click connection. This makes it easy to install the mounting rail from above.

3 Integrated cable management

Cables and connectors are neatly and securely held in place with the cable clip. You can also simply click the optimizer onto the cable clip.

4 Always the right measurements

The universal module clamp is suitable for solar panels with a frame thickness between 30 and 50 mm. Due to its smart design, this panel clamp can be used as a mid-clamp and as an end clamp (in combination with the end cap).

ROOF FASTENERS



ClickFit EVO Slate Roof Hook 1008042

MOUNTING RAIL



ClickFit EVO Mounting rail Mounting rail 1188mm 1008131 1008132 Mounting rail 2338mm Mounting rail 3488mm 1008133 Mounting rail 3500mm 1008007 Mounting rail 4638mm 1008134 Mounting rail 5770mm 1008135

MODULECLAMP & END CAP



ClickFit EVO Module Clamp Universal grey 1008020



ClickFit EVO Module Clamp Universal black 1008020-B



ClickFit EVO Mounting rail End cap grey 1008060



ClickFit EVO Mounting rail End cap black 1008060-B



ClickFit EVO End Cap without end clamp support grey 1008066 ClickFit EVO End Cap without end clamp support black



1008066-B ClickFit EVO End Clamp Support grey



1008065

ClickFit EVO End Clamp Support black 1008065-B

ACCESSOIRES



ClickFit EVO Mounting Rail Connector Piece 1008061



ClickFit EVO Mounting Rail Cable clip optimiser ready 1008062



ClickFit EVO Auxiliary set with cable clip 1008064



ClickFit EVO bit torx 30 1008069

Calculator

In the Esdec calculator you can manage and calculate all your projects, for both pitched and flat roofs. One platform with all Esdec mounting systems for the most reliable calculation of your project.

Save time: manage all your projects on one platform

One calculator for projects on pitched and flat roofs



Unlimited calculations: use the calculator for your own project calculations without limits on the roof height. The calculator also takes into account the terrain category, snow load and wind zone to provide accurate advice, specific to your project.

Go to esdec.com/en/calculator

÷	-
×	Ε

Warranty

ClickFit EVO meets all of the requirements and standards that currently apply. ClickFit EVO comes with a unique 20-year product warranty, thus ensuring the system's quality.

- \checkmark Use of premium high tech materials
- \checkmark Extensively tested
- **BDA/KIWA** certification \checkmark
- 20 years' product warranty



Esdec

Londenstraat 16 7418 EE Deventer Nederland

↓ +31 850 702 000
 ⋈ info@esdec.com

BUILDING VALUE FOR SOLAR PROFESSIONALS