

Certificate

subject:	ESDEC Calculator FlatFix Fusion 2021
date:	February 7 th , 2022
reference:	MvU/MvU/W 15389-26-NO-001
from:	ir. G.M. van Uffelen
to:	Esdec B.V.

This certificate concerns an evaluation of the ESDEC Calculator for ballast calculations for the FlatFix Fusion system, that is depicted in the photographs down here.



This is based on the specific wind tunnel research conducted by Peutz bv into the wind load on the Esdec FlatFix Fusion mounting system for flat roofs. This dedicated wind tunnel study, specifically for this system, was carried out by us in 2018. The lower left photograph shows the scale model in our wind tunnel.



Based on mechanical lift tests carried out by Esdec with improved system connections in the summer of 2021, see right photograph up here, the actual degree of interconnection of the systems was determined and processed by us into the wind tunnel data. These have been

peutz bv, postbus 66, 6585 zh mook, +31 85 822 86 00, mook@peutz.nl, www.peutz.nl kvk 12028033, conditions in accordance with DNR 2011, member NLingenieurs, btw NL.004933837B01, ISO-9001:2015



incorporated in the aforementioned calculator of Esdec. A screendump has been depicted down here.

	ROOF 1	¥ +	OVERVIEV	w																											
	DCATION		X DRA	AW ROO	F	∰ AI	DD PA	NELS	•	æ	AUTO	FILL	PANE	LS	0 0	RAW	OBSTA	CLE	D		×	Ŧ,	Q	e	J	c	e :	8	SUMMARY	l i i i i i i i i i i i i i i i i i i i	
	THE NETH																								10	1.1.1	111		WIND PRESSUI	RE	731.99 N/r
	memer	intercontros :														111													PANEL COUNT		360
TEBRAN CATEGORY I Image: Control of the state of t	WIND ZO															46m													TOTAL POWER		122.40 kV
OV Image: Control of the control of																														LOAD OVER	16.17 kg/
Note: Note: <th< td=""><td>TERRAIN CAT</td><td>EGORY II ·</td><td></td><td>64</td><td></td><td>~</td><td></td><td>-</td><td></td><td>~</td><td></td><td>~</td><td></td><td>~</td><td>~</td><td>-</td><td></td><td>~</td><td></td><td>~</td><td></td><td>~</td><td></td><td>~</td><td></td><td>~ ~</td><td>·</td><td></td><td>TOTAL WEIGHT</td><td></td><td>12,926.7</td></th<>	TERRAIN CAT	EGORY II ·		64		~		-		~		~		~	~	-		~		~		~		~		~ ~	·		TOTAL WEIGHT		12,926.7
FAR* Value	OF				en 1			_	~	_			~				~		_		••				~		_		YOUR CONF	CURATION	
FAT isin					_	-	_	\rightarrow		36g			_		_	_		364				344		_			_			GURATION	
BTUME INSULATED * MOLE NOFORMULATED * NOFORMULATED	FL	AT *		-	_				_	_	369				**	-			360				369		_	-	·		PRODUCT	FLATFIX FU	JSION -
Interfact Interfact <t< td=""><td>BITUMEN I</td><td>NSULATED *</td><td></td><td></td><td>~</td><td></td><td></td><td>-</td><td>244</td><td></td><td></td><td>244</td><td>344</td><td></td><td>~</td><td></td><td>~</td><td></td><td></td><td>364</td><td>*•</td><td></td><td></td><td>344</td><td>-</td><td>-</td><td></td><td></td><td>BLACK (WHEN</td><td></td><td></td></t<>	BITUMEN I	NSULATED *			~			-	244			244	344		~		~			364	*•			344	-	-			BLACK (WHEN		
0 0	IGHT	ANGLE		-		-				364				64		**		364				264				~	_				
Not of cliest raise Not of cliest rais Not of cliest raise Not of cliest rai	10 🗘 m	0 0	[25m]				-				364								364				384				_	25m	AND/OR		
No No <th< td=""><td>PADET HEIGHT</td><td></td><td></td><td></td><td>_</td><td>_</td><td>_</td><td>-</td><td>_</td><td>_</td><td></td><td>264</td><td>_</td><td></td><td>~</td><td>_</td><td></td><td></td><td></td><td>264</td><td></td><td></td><td></td><td>264</td><td></td><td>-</td><td>· .</td><td></td><td></td><td></td><td></td></th<>	PADET HEIGHT				_	_	_	-	_	_		264	_		~	_				264				264		-	· .				
NELS No <				~	~				364				384			~	~				244			_	364		_		-		
NELS I					_	-		_	_	36g			_	-				364	_			264		_	_		_				
NNO CHEETAN HONO ZULYER FRAME - No	NELS				_	_	_	_	_		384		_		~				384				384	_	_		·				
Mark Control (1) Mark Control (1)<				-		_	_	_	_			264	_							364				384			_				x 700
Instrume Instrum Instrume Instrume				1.284		P-254p	P 234g			P-334g	Pathy	P 284	_	P 334g	1.384	1384		P 354	Pathy	P-254g		P-204	P.25q	P 204		P 254 p 455.4	-				x 780
Office 1664 mm 1004335 Flatfix end clamp 12 Oracis 13 Nag Effen 25mn 200711 124Fix Fixed clamp 12 Column 35 mm 200711 124Fix Fixed clamp 26		1002 mm																													p 660
off 10.7 kg Ham 35mm contests 35 mm 1007011 Plantin Fusion base 26																															120
100/011 Flathix Fusion base 26		-														46m															
	KNESS	35 mm 340 Wp																											1007011 Fla	tFix Fusion base	26

We hereby declare, after studying and testing the calculator, that Esdec does indeed use the wind tunnel measurements of FlatFix Fusion, which have been combined with the mechanical lift tests into the wind tunnel data, and that the results have been correctly and safely processed in the Esdec calculator. The approach and method used by Esdec when applying this calculator have been tested and approved by us in several reference projects.

Conformity: CUR Recommendation 103: 2005 NEN 7250: 2021 NEN-EN 1990: 2011 NEN-EN 1991-1-4: 2019

Mook,

This certificate contains 2 pages

'**______.